
# Technical Data Sheet

## ODS-AGM28LMJA




- Metal Jacket; right positive SAE brass posts with 3/8 inch threaded receptacle
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

## Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

## Charging and Self-Discharge

| | |
|---|---|
| Cyclic Charge Voltage | 14.4 - 14.8V @ 25ºC |
| Float Charge Voltage | 13.5 - 13.8V @ 25ºC |
| Charger voltage at 68°F (20°C) | 14.4V to 14.8V |
| Self-discharge per month at 68°F (20°C) | 1.25% |
| Self-discharge per month at 104°F (40°C) | 5% |
| 80% depth of discharge cycles | 400 |

## Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

## Power and Performance

| | |
|---|---|
| Voltage | 12V |
| Pulse (5 second) Hot Cranking Amps (PHCA) | 900A |
| Cold Cranking Amps (CCA) | 330A |
| HCA | 610A |
| MCA | 480A |
| 20Hr Nominal Capacity (Ah) | 28Ah |
| 10Hr Nominal Capacity (Ah) | 27Ah |
| Reserve Capacity Minutes | 48 mins |
| Terminal | SAE |
| Torque Spec in-lbs (Nm max) | N/A |
| Internal Resistance (mΩ) | 5 mΩ |
| Short Circuit (A) | 2400A |
| Recommended Min. Charging Current (A) | 2.7A |
| UPC | 635241141054 |

## Dimensions and Weight

| | |
|---|---|
| Length | 6.6 in / 168 mm |
| Width | 7.1 in / 180 mm |
| Height (terminals included) | 5.8 in / 147 mm |
| Height (container) | 5 in / 127 mm |
| Weight | 25.3 lbs / 11.5 kg |

**See Line Drawing on next page**

## Temperature

| | |
|---|---|
| Operating temperature range | -40°F / -40°C to 176°F / +80°C |
| Optimum storage temperature | 68°F / +20°C |

Technical Data Sheet correct at time of exporting PDF. Please check website for updates.

**EnerSys World Headquarters**
2366 Bernville Road
Reading, PA 19605, USA
Tel: +1-800-964-2837

**EnerSys EMEA**
EH Europe GmbH
Baarerstrasse 18
6300 Zug, Switzerland

**EnerSys Asia**
No. 85, Tuas Avenue 1
Singapore 639518
Tel: +65 6558 7333

**Want more info? Scan code to access the ODYSSEY® Battery Literature Library**

© 2025 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E.



PDF Generated at https://eu.odysseybattery.com 09/05/2025 08:31:31

# Technical Data Sheet

# ODS-AGM28LMJA

## Line Drawing




## ODYSSEY batteries – AGM² Thin Plate Pure Lead (TPPL) Technology

ODYSSEY® AGM² Thin Plate Pure Lead (TPPL) batteries feature 99% pure lead plates that are extremely thin, so more of them fit into the battery. More plates mean more power – ODYSSEY AGM² TPPL batteries deliver twice the power and three times the service life of any other conventional battery, outperforming standard AGM or SLI (flooded) batteries in terms of power density, fast-charge acceptance, shelf life, durability and most important – value for your money.

Technical Data Sheet correct at time of exporting PDF. Please check website for updates.


**EnerSys World Headquarters**
2366 Bernville Road
Reading, PA 19605, USA
Tel: +1-800-964-2837

**EnerSys EMEA**
EH Europe GmbH
Baarerstrasse 18
6300 Zug, Switzerland

**EnerSys Asia**
No. 85, Tuas Avenue 1
Singapore 639518
Tel: +65 6558 7333


**Want more info?**
**Scan code to access the ODYSSEY® Battery Literature Library**


© 2025 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E.