Article Data Sheet

Generated on 23.01.2025, 01:51

VARTA Motion Sensor Outdoor Light Twin Pack w/o. Batt.





Let's go outdoors: Compact and lightweight LED outdoor light with splash water and dust protection (IP44), motion sensor and two different light levels. Thanks to a screw hole, strong magnets and 3M adhesive tape, the light can be flexibly mounted.

4 0 0 8 4 9 6 0 6 5 0 8 0

Information

- Compact and lightweight
- Splash water resistant (IP44) and shock proof (1m drop test)
- Warm white LED for pleasant illumination
- Motion sensor detector to activate light
- Motion recognition within 3m and an angle of 120°
- Auto shut off after 30 seconds
- Slide switch on bottom to choose mode (On, Off, Auto, High, Low)
- Convenient installation by offering three options: hook hole, magnet and 3M adhesive tape
- 3x AAA batteries for each light not incl.

Article Details

Ordernumber	16634 101 402
Customs Tariff Number	94054231
Country Of Origin	China
Beam Range	7.00 m
Runtime	60 h
Total light output	40 lm
Product Length / Depth mm	63.00
Product Width mm	25.00
Product Height mm	96.00
Product Weight g	60.20

Logistical Data

	Content (SU)	GTIN / EAN	Facing (mm)	Depth (mm)	Height (mm)	Weight (kg)
VBE (Selling unit)	1	40 08496 065080	168.00	31.00	237.00	0.17
SK2 (Inner carton 2)						
SK1 (Inner carton 1)						
VSK (Master carton)	4	40 08496 065097	275.00	200.00	76.00	0.80
PAL (Pallet)	780	40 08496 065103	800.00	1,200.00	1,138.00	176.73

Layer / Pallet	Master carton / Layer	Master carton / Pallet	Minimum pieces / shipment unit
13	15	195	4

All mentioned products and specifications are subject to change. In case of non-availability of any product or item, VARTA Consumer Batteries GmbH & Co. KGaA cannot be held responsible. Some of the products shown may not be available in all countries. The pictures might be different to the original products. Technical changes and errors reserved.

VARTA Consumer Batteries GmbH & Co. KGaA | Alfred-Krupp-Str. 9 | 73479 Ellwangen | Germany
P.O. Box 1363 | 73473 Ellwangen | Germany | Phone (+49) 7961 83 0 | Fax (+49) 7961 83 440